


3/5 Port Hand Valve Series TAC




◆ Specifications

Model	TAC-31R.V.P. TAC-41R.V.P.
Port size	1/8
Fluid	Air
Flow area	5.5mm ²
Operating pressure range	0~1.0 MPa
Proof pressure	0~1.5 MPa
Ambient and fluid temperature	0~70°C



◆ How to Order



Button type

V	Pin lever type
P	Push Button type
R	Roller type

Type of actuation

31	3 port 2 position	41	5 port 2 position
----	-------------------	----	-------------------

Model

TAC	3/5 Port Hand Valve
-----	---------------------

◆ Dimensions

<p>TAC-31R</p>	<p>TAC-31V</p>	<p>TAC-31P</p>
<p>TAC-41R</p>	<p>TAC-41V</p>	<p>TAC-41P</p>

II

- VF
- SY
- SYJ
- 4V100
- 4V200
- 4V300
- 4V400
- VT307
- VP
- 3V
- 2W
- 2WH
- 2L
- 2V
- 2P
- VFA
- SYA
- 4A100
- 4A200
- 4A300
- 3A100
- 3A200
- 3A300
- 3L
- 4L
- 4H
- SL,SH
- 4HV
- HV,K
- 3FM
- 3F
- 4F
- FV
- MSV
- MOV
- JM
- TAC
- HSV
- RE
- ASC
- KA
- ACV
- KS
- QE
- Manifold